

Motability Retail Prescription Form

Yes, you can:

Tel: 01656 776222 Email: ordersuk@invacare.com Online Spares available at: www.invacare.co.uk JANUARY 2025 Customer Ref:

| Customer Ref* | Account No* |
|-------------------|-------------|
| Contact No* | Order No* |
| Delivery Address* | Order Qty* |
| | Order date* |

AVIVA RX20 Modulite M21 707041 - Weekly Price £48.27

Standard Features

- Max user weight 136kg (21 Stone)
- Crash tested ISO 7176 -Part 19
- Modulite seating system
- Flex3 adjustable Backrest Plates with Laguna Backrest cushion
- Standard T-Armrests, detachable with Long armpad
- Manually settable Seat Tilt 0 15°
- Manual Settable Recliner (in 3.75° steps) 90° 120°
- 80° hangers with fixed footplate
- Remote LiNX DLX-REM110 with swing away bracket
- 8" Castor, puncture proof solid tyre
- Solid inlay black wheels
- 6 km/h 4mph motors
- 60Ah batteries
- Anti tippers
- 4 Point tie down system
- · Lapbelt with autolock (adjustable both sides)

Please make your selection with a cross in the box

Standard Base price: £5,977



standard feature POA special request

| Customer wei | ht = KG | | |
|---------------|---|-------|--|
| Code | Description | | |
| BASE MODEL | | | |
| JBC0000 | AVIVA RX 20 Base Model Max user weight up to 136 kg | 5,977 | |
| CHASSIS WID | 'H* | | |
| JBL2810 | Chassis Narrow (560 mm/22") | • | |
| SEATING TYPE* | | | |
| JBC2100 | Invacare® Modulite Seat Unit | • | |
| SEAT FRAME | | | |
| JBC2111 | Telescopic Seat Frame and Plate with Side Rails | • | |

O Free of charge

| SEAT WIDTH* | | |
|---------------|---|---|
| JBC2121 | 380 mm Seat Plate | Q |
| JBC2122 | 430 mm Seat Plate | 0 |
| | | |
| JBC2123 | 480 mm Seat Plate | O |
| JBC2124 | 530 mm Seat Plate | O |
| SEAT DEPTH* | | |
| JBC2132 | Seat Depth 410 mm | O |
| JBC2134 | Seat Depth 460 mm | 0 |
| JBC2136 | Seat Depth 510 mm | 0 |
| SEAT CUSHIO | N* | |
| JBC2142 | Matrx Flo-tech Cushion Flo-tech Lite | • |
| BACKREST SU | IPPORT* | |
| JBC2162 | Backposts tall (540 mm) | • |
| PUSH HANDLE | S FOR BACKPOSTS | |
| JBC2108 | Backposts without push handles | • |
| BACKREST UP | PHOLSTERY / CUSHION* | |
| JBC2173 | Flex3 adjustable Backrest Plates with Laguna Backrest cushion | • |
| UPHOLSTERY | TYPE* | |
| JBC2152 | Black Black multi stretch PU coated fabric Upholstery Upholstery | 0 |
| JBC2155 | Black Spacer Fabric Upholstery | O |
| ARMREST (Pai | r)* | |
| JBC2191 | T-Arm detachable, Standard | • |
| ARMPAD (Pair) |)* | |
| JBC2196 | Long Armpad (375 mm) | • |
| SEAT LIFTER / | SEAT TILT* | |
| JBC1091 | Manually settable Seat Tilt 0 - 15° | • |
| SEAT TO GRO | UND HEIGHT* | |
| JBC2857 | Seat-to-Floor Height 435 mm | O |
| JBC2858 | Seat-to-Floor Height 460 mm | O |
| JBC2859 | Seat-to-Floor Height 485 mm | 0 |
| BACKREST RE | CLINER* | |
| JBC0975 | Manual Settable Recliner (in 3.75° steps) 90° - 120° | • |
| FOOTREST HA | NGER TYPE* | |
| JBC0526 | Standard hanger 80° pair Lower leg length: 350 - 450 mm | • |
| FOOTPLATE T | YPE* | |
| JBC0512 | Fixed Footplate pair | • |
| CONTROLS* | | |
| JBC2201 | Remote LiNX DLX-REM110 = Drive only 1 Drive function with Drive only power module | • |
| CONTROL BRA | ACKETRY* | |
| JBC1707 | Swing Away Bracket RH | O |
| JBC1708 | Swing Away Bracket LH | 0 |
| | 1 | |

| SHROUD COLC | DUR* | |
|-------------------|---|----------|
| JBC2871 | Mid range - Black/Anthracite Shroud | 0 |
| JBC2872 | Mid range - Silver Shroud | O |
| JBC2873 | Mid range - Bengal Red Shroud | O |
| JBC2874 | Mid range - Mercury Blue Shroud | O |
| JBC2875 | Mid range - Midnight Purple Shroud | O |
| RIM COLOUR* | wild runge winding it i diplo of load | |
| JBC2882 | Mid range - Black Rim Inserts | 0 |
| JBC2883 | Mid range - Silver Rim Inserts | O |
| JBC2884 | Mid range - Bengal Red Rim Inserts | · · |
| JBC2885 | Mid range - Mercury Blue Rim Inserts | 0 |
| JBC2886 | Mid range - Midnight Purple Rim Inserts | 0 |
| FORKS* | Mid range - Midnight Fulple Killi lisets | |
| JBC2632 | Double sided fork Without castor rim insert (enlarges wide base to 656 mm) | • |
| FRONT WHEEL | * | |
| JBC0828 | 8" (200 mm) x 2.50-4 (65 mm) Castor, puncture proof solid tyre | • |
| DRIVE WHEEL* | | |
| JBC0705 | DW 14" (355 mm) x 3" (75 mm), Solid inlay Dual density foam insert | • |
| C.T.C SUSPENS | | |
| JBC2870 | CTC Suspension Control - Traction - Comfort | * |
| SUSPENSION S | | |
| JBC1910 | Soft (suggested for up to 70 kg User Weight) | 0 |
| JBC1912 | Medium (suggested for up to 90 kg User Weight) | O |
| JBC1911 | Firm (suggested for up to 110 kg User Weight) | O |
| JBC1915 | Very firm (suggested for up to 136 kg User Weight) | 0 |
| MOTOR TYPE* | | |
| JBC1282 | 6 km/h | • |
| BATTERY TYPE | | _ |
| JBC1259 | 60 Ah Gel | |
| CHARGER* JBC1343 | Opti Charge Charger 8A (IP44) | _ |
| ANTI-TIPPERS* | | |
| JBC1205 | Anti-tipper | • |
| TRANSPORTAT | | * |
| JBC1494 | 4-Point tie-down (Tested version for using wheelchair as a vehicle seat according to ISO 7176-19) Adequate headrest is compulsory | * |
| LAP BELT* | | |
| JBC2113 | Lap belt with Auto Lock Flexible mount in side rails | • |

TOTAL PRICE

Non Conforming Options:



For a more complex customer requirement please refer to our Invacare Unique special order form. email specialsuk@invacare.com

| Special Instructions Please supply the following information: | | | | | |
|--|--------|--|--|--|--|
| Name: | Email: | | | | |
| Phone: | | | | | |
| Description of special request (please include relevant option code or part number): | | | | | |